

Safety*Link®* First Man Up Strop

Safety**Link's** Strop is used as a first man up system; reduces the amount of step anchors required.







Safety *Link* Pty Ltd **1300 789 545** +61 2 4964 1068 info@safetylink.com

'Innovative Fall Protection'



Safety Link Strop hook with warning tag

Secures the attachment point of the strop when not in use, ensuring the wind cannot blow the strop away from the access point.

- To be used with the first man up system.
- Please note this is not a load rated anchor, only to be used as an accessory to secure the strop.
- N Hook can be secured with 2 screws or 2 rivets.
- Sprung Gate for easy and secure use.



Benefits of choosing Safety Link:

- Used as the first man up system; reduces the amount of step anchors required.
- Sizes range from 1m, 1.5m, 2m, 2.5m, 3m, 3.5m, 4m, 4.5m, 5m and 6m. Contact SafetyLink for site specific required lengths.
- Quicklink must be attached to a load rating anchor.
- Attachment end should be secured with a strop hook when not in use to ensure it can be accessed from a safe area for next use.

Safety *Link* will provide you with the following:

- All products tested and manufactured to Australian and New Zealand Standards.
- All distributors and installers are trained to use Safety Link products.
- Supply installation guides, testing results and product sheets.
- Products tested using a qualified and reputable testing authority.
- N Supply a large range of roof anchors that protect you from the ground up, allowing complete access to your roof.

Installers are qualified to do yearly inspections on your anchors as per Australian and New Zealand Standards.



Safety *Link* Pty Ltd **1300 789 545** +61 2 4964 1068 info@safetylink.com



www.safetylink.com