





Catalogue



Anchor Layout
Video



TileLink Install Video



Safety Centre
Training







SafetyLink's team designed the TileLink roof anchor (winner of an episode on ABC1 The New Inventors) with unique energy absorbing capabilities, to reduce the risk of injury to the person and damage to the structure.

- Fast simple unit for installation, fall protection whilst working at heights.
- Low profile reflective design is a plus for any commercial or residential enterprise wanting to maintain an aesthetically pleasing façade.
- Designed for use on steel rafters under tiles, no need to cut sarking, eliminating waterproofing issues.
- Install with three (3) alternate fixing rows: use 5 x use 8mm Tri-fold Rivets (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip) or 5x 14 gague roofing all thread screws.
- Highly flexible design ensures installation to the majority of roof tile profiles.

WHAT AM I USED FOR?

A height safety anchor point designed for use on steel rafters with tiled roof, will arrest from any direction.

STANDARDS

Complies with: AS/NZS 1891.4 and EN 795:2012.



Product Code	Description	Weight (kg)	Rated	Material
TILEL001_SFM	Rafter Mounted Anchor SFM	0.630	15kN	316 Stainless Steel
TILEL001+Rivets	Rafter Mounted Anchor + 5 Rivets	0.669	15kN	316 Stainless Steel

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-85 Version: 17.0