



- SafetyLink's patented WindowLink is an anchor point designed for use in concrete structures where the eyebolt will remain concealed until needed for use.
- The WindowLink can be placed outside or within the building, creating easy access for window maintenance.
- Non obtrusive concrete anchor designed to swivel 360 degrees.
- Built in shock absorber with discreet stainless steel cover.
- Must be chemically fastened, recommended chemical is Fischer FIS-V.

## STANDARDS

Complies with AS/NZS 1891.4 and EN 795:2012.

## **COMPLETE UNIT - PRODUCT CODE: WINDW001**

Product Parts	Description	Qty	Weight (kg)	Material
WINDW001	WindowLink Complete Unit/Floor-Wall Link	1	0.474	316 SS

## Testing for concrete mounted anchor.

To comply with current Standards each Concrete unit must be tested after installation. Allow required curing time as specified in manual before testing. Test consists of pull out force to 50% of design load of anchorage. *Note: Drilled-in anchorages such as friction and glued-in anchorages shall be placed so that the shear load is at least twice the tension load. For collared eyebolts this translates to a pull at an angle not exceeding 20 degrees to the surface in which the bolt is installed.* 

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



## © 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on <u>ip@safetylink.com</u> and quote the product code.

Doc ID: MKT-94 Version: 15.0

Asia-Pacific/The Americas info@safetylink.com Europe/Africa/Middle East europe.sales@safetylink.com Northern Europe

uk.sales@safetylink.com





www.safetylink.com



Catalogue



Anchor Layout Video



Chemical Adhesive Data Sheet



Safety Centre Training

