







Anchor Layout Video



Safety Centre
Training

DATA SHEET



CLASSIC SURFACELINK

Aluminium Surface Mounted Anchor



- Multi-directional fall protection.
- Suits a multitude of roof profiles.
- Surface mounted anchors <u>must not</u> be used for rope access (abseiling).
- Install using 10 x 8mm Rivets (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip).
- The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.

STANDARDS

Complies with AS/NZS 1891.4.

WHAT AM I USED FOR?

An anchor point designed for use on metal roof sheet profiles where access to timber is difficult. Adjustable design to suit different roof profiles.



COMPLETE UNIT - PRODUCT CODE: ASURF001 + RIVETS			Weight: 0.967kg
Product Parts	Description	Qty	Material
EYEBOLT-SURFACELINK	SurfaceLink Eyebolt	1	316 Stainless Steel
NUT LOCKING HEX	Locking Hex Nut	1	316 Stainless Steel
ADV-PLATE-AL-305-H	SurfaceLink Plate: 305x243x3mm (Holes)	1	Aluminium
WASHER 70od-Plastic	Washer: 70 OD	1	Plastic
WASHER 50od-SS	Washer: 50 OD	1	316 Stainless Steel
WASHER M16_SPRING	Spring Washer: M16 316SS	1	316 Stainless Steel
NUT M16	Nut: M16	1	316 Stainless Steel
FOAM-TAPE 29 cm	Adhesive single sided tape	2	Foam
Rivet 8mm(27.7)	Aluminium 8mm Tri-fold Rivets	10	Aluminium

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-57 Version: 15.0