

SURFACELINK

Surface Mounted Anchor



www.safetylink.com



Catalogue



Anchor Layout Video



Safety Centre Training

DATA SHEET



FS 70792



- SurfaceLink with adjustable plate design to suit different roof profiles.
- Surface mounted anchors must not be used for rope access (abseiling).
- Install using 12 x 8mm Rivets (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip range, Aluminium).
- The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.

STANDARDS

Complies with AS/NZS 1891.4.

WHAT AM I USED FOR?

An anchor point designed for use on metal roof sheet profiles where access to timber is difficult. Adjustable design to suit different roof profiles.



COMPLETE UNIT - PRODUCT CODE: SURFL001+RIVETS			Weight: 1.999kg
Product Parts	Description	Qty	Material
EYEBOLT-SURFACELINK	SurfaceLink Eyebolt	1	316 Stainless Steel
NUT LOCKING HEX	Locking Hex Nut	1	316 Stainless Steel
SURF-SIDEPLATE	SurfaceLink Side Plate	2	316 Stainless Steel
WASHER 70od-SS	Washers: 70 O.D.	2	316 Stainless Steel
WASHER M16_SPRING	Spring Washer: M16	1	316 Stainless Steel
NUT M16	Nut: M16	1	316 Stainless Steel
Rivet_8mm(27.7)	Rivets: 8mm Tri-fold	12	Aluminium

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-67 Version: 16.0

Asia-Pacific/The Americas
info@safetylink.com

Europe/Africa/Middle East
europa.sales@safetylink.com

Northern Europe
uk.sales@safetylink.com