



SCAN ME  
Terms and  
Conditions



SCAN ME  
Website



SCAN ME  
Catalogue

DATA SHEET

# ABSEIL EYEBOLT



- The Abseil Eyebolt is designed to withstand a live load without activating the bending motion that occurs when arresting a fall.
- Abseiling eyebolts are to be used for rope access (abseiling and fall arrest).
- Available to attach to a multitude of different mounting systems (not to be used with surface mounted anchors).
- 360° Multi-directional.
- Single person anchor, rated at 15kN.
- Thread M16.
- Eyelet 28mm ID.

## STANDARDS

Complies with AS/NZS 1891.4.

## WHAT AM I USED FOR?

The **Abseiling Eyebolt** is a fall arrest anchor which uses the same tapered design as the standard eyebolt but incorporates a shorter shaft enabling the eyebolt to withstand a live load without activating the bending motion that occurs when arresting a fall.

All safety procedures must comply in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety system.

### COMPLETE UNIT - PRODUCT CODE: EYEBT002

Product Parts	Description	Qty	Weight (kg)	Material
EYEBOLT-ABSEIL	Abseil Eyebolt	1	0.220	316 Stainless Steel
NUT M16	Nut: M16	1	0.029	316 Stainless Steel
			<b>0.249</b>	

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

**Patents:** SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on [ip@safetylink.com](mailto:ip@safetylink.com) and quote the product code.

Doc ID: MKT-25 Version: 13.0

[www.safetylink.com](http://www.safetylink.com) | [info@safetylink.com](mailto:info@safetylink.com) | 1300 789 545 | +61 2 4964 1068



FS 707792