



DATA SHEET

Standard Eyebolt



- ▲ Standard eyebolts must only be used as a fall arrest anchor.
- ▲ Unique energy absorbing capabilities, protecting structures and users in the event of a fall.
- ▲ Available to attach to a multitude of different mounting systems.
- ▲ 360° Multi-directional.
- ▲ Single person anchor, rated at 15kN.
- ▲ Thread M16.
- ▲ Eyelet 28mm ID.

STANDARDS

Complies with AS/NZS 1891.4.

WHAT AM I USED FOR?

The **Standard Eyebolt** is designed for fall arrest, it's long tapered stem is designed to absorb energy while arresting a fall therefore reducing the load off the structure and the person. The length of the eyebolt enables the attachment point to project above the roof structure when installing into different bases for timber structures. The standard eyebolt is not designed for a constant live load.

All safety procedures must comply in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety system.



SCAN ME

www.safetylink.com



SCAN ME

Catalogue



SCAN ME

Safety Centre
Training

COMPLETE UNIT - PRODUCT CODE: EYEBT001

Product Parts	Description	Qty	Weight (kg)	Material
EYEBOLT-STANDARD	Standard Eyebolt	1	0.263	316 Stainless Steel
LOCKING HEX NUT	Locking Hex Nut: M16	1	0.039	316 Stainless Steel
			0.302	

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-52 Version: 15.0