

- ▲ Lockable gate to restrict access to caged ladder.
- ▲ Use padlock to secure (padlock is not provided).
- ▲ Heavy gauge aluminium for superior strength.
- ▲ FastFit ladder system is designed for single person use and rated for maximum 150kg.
- ▲ FastFit ladders are manufactured to AS 1657:2018 Standards.

### COMPLETE UNIT - PRODUCT CODE: LADER002.CAGE.GATE

**Weight: 4.111 kg**

Product Code	Description	Qty	Material
LADER002.CAGE.GATE.01	Gate	1	Aluminium
LADER002.CAGE.GATE_LOCK	Lock Plate	1	Aluminium
BOLT-M8x30mm Cup HD	Bolts: M8 x 30mm Cup Head	3	316 Stainless Steel
NUT M8 Flanged_316	Flanged Nut: M8	3	316 Stainless Steel



SCAN ME  
Manual



SCAN ME  
Website



SCAN ME  
Catalogue



SCAN ME  
Safety Centre  
Training


### Ladder examples below



LADERK002.042



LADERK002.042+BASE



LADERK002.052



LADERK002.052+BASE

**A FALL RESCUE PLAN SHOULD BE DEVELOPED PRIOR TO USING SAFETYLINK EQUIPMENT**

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on [ip@safetylink.com](mailto:ip@safetylink.com) and quote the product code.

Doc ID: MKT-891 Version: 8.0