








INSTALLATION HANDBOOK


SURFACELINK ANCHORS

SafetyLink is an innovative anchor company achieving success and keeping you safe whilst working at heights.

-  ROOF ANCHORS
-  HORIZONTAL LIFELINES
-  PERMANENT LADDERS
-  LADDER STABILISERS
-  TEMPORARY ANCHOR
-  WALKWAY & GUARDRAIL
-  X-RAIL - HORIZONTAL RAIL



Read entire handbook before installing SafetyLink products. All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd. Failure to follow all warnings and instructions may result in a serious injury or death.



Asia-Pacific/The Americas
info@safetylink.com
Europe/Africa/Middle East
europe.sales@safetylink.com
Northern Europe
uk.sales@safetylink.com

www.safetylink.com

INSTALLATION OF SAFETYLINK SURFACELINK ANCHORS

WARNINGS.....	3
MAINTENANCE – PERIODIC INSPECTIONS.....	4
WARRANTIES.....	5
CLASSIC SURFACELINK ANCHOR	6
POSITIONING OF SURFACELINK ANCHOR POINT (<i>REFER TO APPENDIX DIAGRAM 2</i>)	6
COMPONENTS	6
INSPECT THE INTEGRITY OF THE STRUCTURE AND ROOF SHEETING.....	7
INSTALLATION ON STANDING SEAM / KLIP-LOK ROOF PROFILES	7
ASSEMBLING	8
INSTALLING.....	9
SURFACELINK ANCHOR STAINLESS STEEL – DOUBLE PLATES	10
POSITIONING OF SURFACELINK ANCHOR POINT (<i>REFER TO APPENDIX DIAGRAM 2</i>)	10
COMPONENTS	10
ASSEMBLING	11
INSTALLING.....	12
SURFACELINK ANCHOR STAINLESS STEEL – BROWNBUILT	13
POSITIONING OF SURFACELINK ANCHOR POINT (<i>REFER TO APPENDIX DIAGRAM 2</i>)	13
COMPONENTS	13
ASSEMBLING	14
INSTALLING.....	15
APPENDIX – DIAGRAM 2 – ANCHOR POSITIONING LAYOUT.....	16
EXPERT FALL PROTECTION PLANNING	17
NOTES	18
NOTES	19
IN CASE OF ACCIDENT	20



Safety Centre
Training



Anchor Layout Video



Catalogue



Website



WARNINGS



READ CAREFULLY SOMEONE'S LIFE DEPENDS ON IT

INSTALLATION MUST BE CARRIED OUT BY, OR UNDER THE SUPERVISION OF A COMPETENT HEIGHT SAFETY INSTALLER.

The building or structure for the anchorages should be assessed by an engineer, unless it is clear to a competent height safety installer that the anchorages system is structurally adequate.

STANDARD EYEBOLTS MUST ONLY BE USED AS A FALL ARREST ANCHOR.

ABSEILING EYEBOLTS ARE TO BE USED FOR ROPE ACCESS (ABSEILING).

SURFACE MOUNTED ANCHORS MUST NOT BE USED FOR ROPE ACCESS (ABSEILING).

RETRO EYEBOLTS USED FOR ROPE ACCESS (ABSEILING) EXCEPT ON HIGH PROFILE SECTION.

When installing anchor points all safety procedures must be complied with in accordance with the current safety code/s of practice/s for working at heights.

- Recommended waterproofing for roof tiles: *Sika Flex Co-Polymer Sealant*.
- Recommended waterproofing for metal roof: *Silicone Sealant*.
- A personal energy absorber or a fall-arrest device with a personal energy absorber must be used to connect to all SafetyLink Anchorages and (or) Strops.



MAXIMUM USER PER EYEBOLT IS ONE (1)

WARNING

Locking Hex Nut must be fully screwed up the thread of the eyebolt to expose 30mm of thread.

This thread must be fully screwed into the bracket.

Locking Hex Nut must be firmly tightened onto the bracket to stop the eyebolt from unscrewing and to gain maximum strength.

Locking Hex Nut



EYEBOLTS - Threads need to have a minimum of **SIX FULL 360° TURNS** into the ultimate thread.

RETRO EYEBOLTS - Threads need to have a minimum of **EIGHT FULL 360° TURNS** into the ultimate thread.



CORRECT

Always use a spanner when tightening and un-tightening the locking hex nut.



WRONG

DO NOT place an object into the eye of the eyebolt to tighten or un-tighten the locking hex nut, as this may damage the eyebolt.

MAINTENANCE – PERIODIC INSPECTIONS

All items of height safety equipment which are in regular use shall be subjected to periodic inspection and servicing. These regular scheduled inspections and servicing must be carried out by a competent height safety installer.

FIXED LADDERLINK: LADDER SUPPORT BRACKET

ALL LADDERLINKS MUST BE INSPECTED EVERY 12 MONTHS, INSPECTIONS NEED TO BE CARRIED OUT BY A COMPETENT HEIGHT SAFETY INSTALLER.

Procedures to be followed at inspection time:

- Visually inspect ladder support brackets for any signs of deterioration or the protective coating being removed. *(Note: LadderLink is made from marine grade aluminium and therefore should not corrode).*
- Ensure LadderLink is firmly secured to the structure as per SafetyLink Installation Handbook. *(refer to Installing LadderLink).*

SAFETYLINK ANCHORAGES

ALL ANCHORAGES MUST BE INSPECTED EVERY TWELVE MONTHS, INSPECTIONS NEED TO BE CARRIED OUT BY A COMPETENT HEIGHT SAFETY INSTALLER.

Procedures to be followed at inspection time:

- Visually inspect anchors for signs of deterioration.
- The FrogLink/TileLink anchor point has two energy absorbing regions and two stabilising joins which hold the eyelet in place during use. If these energy absorbing regions are expanded this will indicate the anchor point has arrested a fall. Similarly, if the two stabilising joins have been broken this would also indicate the FrogLink/TileLink has arrested a fall and should be replaced.
- The eyebolt should remain straight, a bent eyebolt will indicate that the anchor point has arrested a fall *(The design features of the eyebolt includes the ability to bend like a fishing pole starting from the top and working its way to the bottom, enabling it to use up energy as the eyebolt bends whilst lessening the force on the person falling and the attachment point).*
- Visually inspect the components of the anchor for corrosion, superficial surface marking is permitted while deeper corrosion or pitting would require attention.
- Manually (by hand) check the eyebolt for rigidity and tightness, if the eyebolt can turn in the anticlockwise direction it will require attention.
- Visually inspect the rubber hat washer and waterproofing components to ensure it has remained sealed.
- Visually inspect the attachment component of the anchorage where practically possible.
- Visually inspect the parent structure for modifications or deterioration which might lead to loss of anchorage strength.
- For Concrete Installation Only: To comply with Australian Standards, each ConcreteLink must be tested after installation and at every recertification inspection. Ensure you wait the recommended curing time as specified by the chemical anchor instructions. The pull test can be done using a 16mm threaded eyebolt. Test consists of ultimate pull out force proof loading to 50% of design purpose of anchorage.
- A personal energy absorber or a fall-arrest device with a personal energy absorber must be used in conjunction with all SafetyLink Anchorages and Lifeline systems.

IN ADDITION TO SAFETYLINK PTY LTD EQUIPMENT, ALL ANCILLARY EQUIPMENT MUST BE INSPECTED IN ACCORDANCE WITH APPLICABLE REGULATORY REQUIREMENTS AND THE MANUFACTURER'S INSTRUCTIONS.



**FOR MAINTENANCE ADVICE AND SERVICES PLEASE CONTACT SAFETYLINK
ON +61 249 641068 OR 1300 789545 FOR YOUR NEAREST SAFETYLINK INSPECTION SERVICE
CENTRE OR EMAIL: info@safetylink.com**



WARRANTIES

EXTRACT: SafetyLink Pty Ltd STANDARD TERMS AND CONDITIONS

- 11.1 To the extent permitted by law all implied conditions, warranties and undertakings are expressly excluded.
- 11.2 Except as provided in this clause the Company shall not be liable for any loss or damage, whether direct or indirect (including consequential losses or damage) arising out of any breach of contract by the Company or any negligence of the Company, its employees or agents.
- 11.3 Should the Company be liable for a breach of a guarantee, condition or warranty implied by the Australian Consumer Law (not being a guarantee, condition or warranty implied by sections 51, 52 and 53 of that Law) then its liability for a breach of any such condition or warranty express or implied shall be limited, at its option, to any one or more of the following.
- A) in case of Goods
 - (I) the replacement of the Goods or the supply of equivalent Goods.
 - (II) the repair of the goods,
 - (III) the payment of the cost of replacing the Goods or acquiring equivalent Goods.
 - (IV) The payment of the cost of having the Goods repaired.Provided that any such Goods are returned to the Company by the Purchaser at the Purchaser's expense.
 - B) in the case of services
 - (i) the supply of the services again,
 - (ii) the payment of the cost of having the services supplied again.
- 11.4 The Company will not be liable for the costs of recovery of the Goods from the field, loss of use of the Goods, loss of time, inconvenience, incidental or consequential loss or damage, nor for any other loss or damage other than as stated above, whether ordinary or exemplary, caused either directly or indirectly by use of the Goods.
- 11.5 The Company warrants that at the time of shipment, Products manufactured by it will be free from defects in material and workmanship. In the absence of a modified written warranty, the Company agrees to making good any such defects by repairing the same or at the Company's option by replacement, for a period of (1) one year from the date of shipment. This limited warranty applies provided that:
- (a) defects have arisen solely from faulty materials or workmanship;
 - (b) the Products have not received maltreatment, inattention or interference;
 - (c) **the Products have been installed in accordance with the Company's Installation Handbooks using only products supplied by the Company;**
 - (d) accessories used with the Products are manufactured by or approved by the Company;
 - (e) the Products are maintained in accordance with Australian Standard 1891.4 (section 9).
 - (f) you notify any claim under this warranty to SafetyLink in writing to the address below no later than 14 days after the event or occurrence concerning the product giving rise to the claim and you pay all costs related to your claim.

This warranty does not apply to any defects or other malfunctions caused to the Goods by accident, neglect, vandalism, misuse, alteration, modification or unusual physical, environment or electrical stress.

Please note that the benefits to the purchaser (as a consumer) given by this warranty are in addition to your other rights and remedies under the Australian Consumer Law. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

- 11.6 If any goods are not manufactured by the Company, the guarantee of the manufacturer thereof shall be accepted by the Purchaser as the only express warranty given in respect of the goods.
- 11.7 Except as provided in this clause 11, all express and implied warranties, guarantees and conditions under statute or general law as the merchantability, description, quality, suitability or fitness of the Products for any purpose or as to design, assembly, installation, materials or workmanship or otherwise are hereby expressly excluded (to the extent to which they may be excluded by law).

PLEASE SEE SAFETYLINK PTY LTD FULL STANDARD TERMS OF CONDITIONS OF SALE FOR FURTHER REFERENCE.



CLASSIC SURFACELINK ANCHOR

Product Code: ASURF001








All safety procedures must be complied with in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety protection system.

⚠ SURFACE MOUNTED ANCHORS MUST NOT BE USED FOR ROPE ACCESS (ABSEILING).

POSITIONING OF SURFACELINK ANCHOR POINT (refer to Appendix Diagram 2)

- The first SurfaceLink must be in a position easily and safely reached from a safe access point. Access to underside of roof is not required for installation.
- It is recommended the SurfaceLink be installed to the top/high section of the roof sheeting profile aligned with the fall of the roof, where this is not practical the SurfaceLink may be installed into the low/pan section, be sure not to create an area where leaves and debris can collect.
- Ensure SurfaceLink is installed between a minimum of two purlins/battens, with the roof sheeting being installed/secured down as per manufacturers recommendations.
- Warning: surface mounted anchor systems installed on concealed fix roof types may require additional roof fixings, please check individual roof sheet type installation manuals.

COMPONENTS

Qty	Product Description	Product
1	Eyebolt: 316 Stainless Steel with Locking Hex Nut	
1	Classic SurfaceLink Plate (305mm Marine Grade Aluminium)	
2	Waterproofing Membrane	
1	Washer: 70mm OD Plastic	
1	Washer: 70mm OD 316 Stainless Steel	
1	Washer: M16 Spring	
1	Nut: M16 316 Stainless Steel	
10	Rivets: 8mm (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip range)	



INSPECT THE INTEGRITY OF THE STRUCTURE AND ROOF SHEETING

- Installation of anchors can only be made to roof sheeting strong enough to support the anchor point.
- **MINIMUM** roof sheet gauge is **0.42mm** for steel and **0.7mm** for aluminium.
- Roof sheets must be inspected thoroughly for splits, rust, corrosion damage and correct installation.
- Ensure the roof sheeting and structure is secured in accordance with current building codes and manufactures instructions.

WARNING: SURFACE MOUNTED ANCHOR SYSTEMS INSTALLED ON CONCEALED FIX ROOF TYPES MAY REQUIRE ADDITIONAL ROOF FIXINGS, PLEASE CHECK INDIVIDUAL ROOF SHEET TYPE INSTALLATION MANUALS.

INSTALLATION ON STANDING SEAM / KLIP-LOK ROOF PROFILES

Surface Mounted Anchor systems installed on concealed fix roof types may require additional roof fixings. Additional securing can be made to roof sheets with 12 gauge roofing screws through the roof sheeting into the purlin/batten, **four (4) above** or **four (4) below** the anchor, on the side of the anchor that falls under two metres from an edge. This secures the roof sheeting in place to the purlins/battens to prevent horizontal movement in the event of a fall.

Note: screws may be required on both sides of the anchor depending on the individual situation.

- ⚠ If any doubt exists with the strength of the structure or roof sheets an engineer should make the assessment.
- ⚠ installation must be carried out by, or under the supervision of a competent height safety installer.
- ⚠ during installation you must be safe at all times.

Live Load on Anchors:

The surface mounted anchor is best suited to roof pitches up to 30 degrees. For over 30 degrees surface mounted anchors should be used in conjunction with other access methods to ensure no live loading. Note: these anchors are not abseil anchors and therefore if they are subjected to a live load this may trigger the energy absorbing regions.




CLASSIC SURFACELINK ANCHOR

Product Code: ASURF001

ASSEMBLING

STEP 1

Apply adhesive waterproofing membrane under rivet location.



STEP 2

Screw locking hex nut into eyebolt leaving 30mm of thread.



STEP 3

Insert eyebolt through Classic SurfaceLink Plate.



STEP 4

Apply a 70mm plastic washer, 70mm stainless steel washer, M16 Spring Washer and M16 Nut to underside of the surface plate, tighten nut finger tight.



STEP 5

Tighten nut and Locking Hex Nut making certain eyebolt lines up with fall of roof.




Threads need to have a minimum of **six full 360° turns** into the ultimate thread.

INSTALLING

1. Place SurfaceLink on surface of roof sheets in required location.
2. Drill Ten (10) 8mm holes into roof sheets through locating holes on both sides of the SurfaceLink (5 each side).
3. Secure the SurfaceLink to the roof by riveting through holes in surface mounted anchor and roof sheet using 8mm Rivets (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip range, Aluminium).

- ⚠ If any doubt exists with the strength of the structure or roof sheets an engineer should make the assessment.
- ⚠ installation must be carried out by, or under the supervision of a competent height safety installer.
- ⚠ during installation you must be safe at all times.



WARNING: SURFACE MOUNTED ANCHOR SYSTEMS INSTALLED ON CONCEALED FIX ROOF TYPES MAY REQUIRE ADDITIONAL ROOF FIXINGS, PLEASE CHECK INDIVIDUAL ROOF SHEET TYPE INSTALLATION MANUALS.

The SafetyLink Anchor Point is now ready for use, giving you an anchor point to attach to while installing the next SafetyLink.

SURFACELINK ANCHOR STAINLESS STEEL – DOUBLE PLATES

Product Code: SURFL001

All safety procedures must be complied with in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety protection system.

⚠ SURFACE MOUNTED ANCHORS MUST NOT BE USED FOR ROPE ACCESS (ABSEILING).




INSPECT THE INTEGRITY OF THE STRUCTURE AND ROOF SHEETING

- Installation of anchors can only be made to roof sheeting strong enough to support the anchor point.
- **MINIMUM** roof sheet gauge is **0.42mm** for steel and **0.7mm** for aluminium.
- Roof sheets must be inspected thoroughly for splits, rust, corrosion damage and correct installation.
- Ensure the roof sheeting and structure is secured in accordance with current building codes and manufactures instructions.

POSITIONING OF SURFACELINK ANCHOR POINT (refer to Appendix Diagram 2)

- The first SurfaceLink must be in a position easily and safely reached from a safe access point. Access to underside of roof is not required for installation.
- It is recommended the SurfaceLink be installed to the top/high section of the roof sheeting profile aligned with the fall of the roof, where this is not practical the SurfaceLink may be installed into the low/pan section, be sure not to create an area where leaves and debris can collect.
- Ensure SurfaceLink is installed between a minimum of two purlins/battens, with the roof sheeting being installed/secured down as per manufacturers recommendations.
- Warning: surface mounted anchor systems installed on concealed fix roof types may require additional roof fixings, please check individual roof sheet type installation manuals.

COMPONENTS

Qty	Product Description	Product
1	Eyebolt: 316 Stainless Steel with Locking Hex Nut	
1	Stainless Steel Side Plates with foam tape	
2	Washer: 70mm 316 Stainless Steel	
1	Washer: M16 Spring	
1	Nut: M16 316 Stainless Steel	
12	Rivets: 8mm (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip range)	



SURFACELINK ANCHOR STAINLESS STEEL – DOUBLE PLATES

Product Code: SURFL001

ASSEMBLING

STEP 1

Screw locking hex nut into eyebolt leaving 30mm of thread.




STEP 2

Add 70mm stainless steel washer to eyebolt thread.




STEP 3

Overlap side plates, aligning slots for Eyebolt.



STEP 4

Insert eyebolt through side plates.



STEP 5

Apply 70mm stainless steel Washer, M16 Spring Washer and M16 Nut, tighten nut finger tight.



Assembling continued over.....


SURFACELINK ANCHOR STAINLESS STEEL – DOUBLE PLATES

Product Code: SURFL001

ASSEMBLING


STEP 6

Adjust side plates and Eyebolt in slot to correct profile of roof.



STEP 7

Tighten nut and Locking Hex Nut making certain eyebolt lines up with fall of roof.



Threads need to have a minimum of **six full 360° turns** into the ultimate thread.

INSTALLING

1. Place SurfaceLink Anchor on surface of roof sheets in required location.
2. Drill twelve 12 x 8mm holes into roof sheets through rivet holes on both sides of the SurfaceLink Anchor.
3. Secure the SurfaceLink Anchor to the roof by riveting through anchor and roof sheet using 8mm Rivets.

- ⚠ If any doubt exists with the strength of the structure or roof sheets an engineer should make the assessment.
- ⚠ installation must be carried out by, or under the supervision of a competent height safety installer.
- ⚠ during installation you must be safe at all times.



WARNING: SURFACE MOUNTED ANCHOR SYSTEMS INSTALLED ON CONCEALED FIX ROOF TYPES MAY REQUIRE ADDITIONAL ROOF FIXINGS, PLEASE CHECK INDIVIDUAL ROOF SHEET TYPE INSTALLATION MANUALS.

Live Load on Anchors:

The Surface Mounted anchor is best suited to roof pitches up to 30 degrees. For over 30 degrees Surface Mounted anchors should be used in conjunction with other access methods to ensure no live loading. Note: These anchors are not abseil anchors and therefore if they are subjected to a live load this may trigger the energy absorbing regions.



SURFACELINK ANCHOR STAINLESS STEEL – BROWNBUILT

Product Code: SURFL001-BROWNBUILT

All safety procedures must be complied with in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety protection system.

⚠ SURFACE MOUNTED ANCHORS MUST NOT BE USED FOR ROPE ACCESS (ABSEILING).


INSPECT THE INTEGRITY OF THE STRUCTURE AND ROOF SHEETING

- Installation of anchors can only be made to roof sheeting strong enough to support the anchor point.
- **MINIMUM** roof sheet gauge is **0.42mm** for steel and **0.7mm** for aluminium.
- Roof sheets must be inspected thoroughly for splits, rust, corrosion damage and correct installation.
- Ensure the roof sheeting and structure is secured in accordance with current building codes and manufacturer's instructions.

POSITIONING OF SURFACELINK ANCHOR POINT (refer to Appendix Diagram 2)

- The first SurfaceLink must be in a position easily and safely reached from a safe access point. Access to underside of roof is not required for installation.
- It is recommended the SurfaceLink be installed to the top/high section of the roof sheeting profile aligned with the fall of the roof, where this is not practical the SurfaceLink may be installed into the low/pan section, be sure not to create an area where leaves and debris can collect.
- Ensure SurfaceLink is installed between a minimum of two purlins/battens, with the roof sheeting being installed/secured down as per manufacturers recommendations.
- Warning: surface mounted anchor systems installed on concealed fix roof types may require additional roof fixings, please check individual roof sheet type installation manuals.

COMPONENTS

Qty	Product Description	Product
1	Eyebolt: 316 Stainless Steel with Locking Hex Nut	
1	Stainless Steel Side Plates BENT with foam tape	
2	Washer: 70mm 316 Stainless Steel	
1	Washer: M16 Spring	
1	Nut: M16 316 Stainless Steel	
12	Rivets (7.7 x 34.0 length, 6.4-15.9 Grip, Yellow seal)	



SURFACELINK ANCHOR STAINLESS STEEL – BROWNBUILT

Product Code: SURFL001-BROWNBUILT

ASSEMBLING

STEP 1

Screw locking hex nut into eyebolt leaving 30mm of thread.




STEP 2

Add 70mm stainless steel washer to eyebolt thread.




STEP 3

Overlap side plates, aligning slots for Eyebolt.



STEP 4

Insert eyebolt through side plates.



STEP 5

Apply 70mm stainless steel Washer, M16 Spring Washer and M16 Nut, tighten nut finger tight.




Assembling continued over.....

ASSEMBLING


STEP 6

Adjust side plates and Eyebolt in slot to correct profile of roof.



STEP 7

Tighten nut and Locking Hex Nut making certain eyebolt lines up with fall of roof.



Threads need to have a minimum of **six full 360° turns** into the ultimate thread.

INSTALLING

1. Place SurfaceLink on surface of roof sheets in required location (minimum of 5mm between top section of roof sheet and SurfaceLink Side Plate).
2. Drill six (6) x 8mm holes into roof sheets through locating holes on both sides of the SurfaceLink; twelve (12) holes in total.
3. Secure the SurfaceLink to the roof by riveting through surface mounted anchor and roof sheet using 8mm Rivets. **These rivets must penetrate through a double layer of roof sheets.**

- ⚠ If any doubt exists with the strength of the structure or roof sheets an engineer should make the assessment.
- ⚠ installation must be carried out by, or under the supervision of a competent height safety installer.
- ⚠ during installation you must be safe at all times.

WARNING: SURFACE MOUNTED ANCHOR SYSTEMS INSTALLED ON CONCEALED FIX ROOF TYPES MAY REQUIRE ADDITIONAL ROOF FIXINGS, PLEASE CHECK INDIVIDUAL ROOF SHEET TYPE INSTALLATION MANUALS.


Live Load on Anchors:

The Surface Mounted anchor is best suited to roof pitches up to 30 degrees. For over 30 degrees Surface Mounted anchors should be used in conjunction with other access methods to ensure no live loading. Note: These anchors are not abseil anchors and therefore if they are subjected to a live load this may trigger the energy absorbing regions.

APPENDIX – Diagram 2 – Anchor Positioning Layout

THIS IS A GUIDE ONLY



All working at heights safety procedures must be complied with when installing SafetyLink anchor points. For more information refer to your state or territories current legislation, regulations, policies and codes of practices.



- ⚠ IF ANY DOUBT EXISTS WITH THE STRENGTH OF THE STRUCTURE OR ROOF SHEETS AN ENGINEER SHOULD MAKE THE ASSESSMENT.
- ⚠ DURING INSTALLATION YOU MUST BE SAFE AT ALL TIMES.
- ⚠ INSTALLATION MUST BE CARRIED OUT BY, OR UNDER THE SUPERVISION OF A COMPETENT HEIGHT SAFETY INSTALLER.


ACCESS, LAYOUT AND USE OF A SAFETYLINK ANCHOR SYSTEM

SafetyLink anchor points are positioned by calculating the pendulum effect, this limits the likelihood of a fall past the edge of the roof space. The pendulum effect still applies to a flat roof.



SPACING MUST BE NO GREATER THAN THE RAFTER LENGTH, PLEASE CONTACT YOUR DISTRIBUTOR IF YOU ARE UNSURE.

SAFETYLINK HEIGHT SAFETY SYSTEMS MUST ONLY BE INSTALLED AS PER OUR INSTALLATION GUIDES, TO STRUCTURES AS SPECIFIED IN THE INSTALLATION MANUAL FOR EACH PRODUCT. SHOULD ANY DOUBT EXIST IN REGARD TO THE STRUCTURES INTEGRITY AN ENGINEER SHOULD BE CONSULTED.



Safety

- Are all areas of your roof protected, allowing complete access when working at heights?
- Are you protected from the ground up, allowing complete access to your roof?
- Detailed comprehensive documentation provided e.g. installation guides, testing results, product sheets should be provided.
- SafetyLink can also provide you with a qualified and reputable installer of SafetyLink products.

1. *Journal of the American Medical Association*, 2000; 284: 2689-2695.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.



Safety**Link**[®]
*Innovative
Fall Protection*



Safety**Link**®
*Innovative
Fall Protection*

IN CASE OF ACCIDENT

- ⚠ **A FALL RESCUE PLAN AND SAFE WORK STATEMENT MUST BE DEVELOPED PRIOR TO USING SAFETYLINK SYSTEMS AND EQUIPMENT.**
- ⚠ **PERSONS WORKING AT HEIGHTS SHOULD NOT WORK ALONE.**

It is critical that before using any SafetyLink Systems a fall rescue plan is in place for any persons suspended mid-air following a fall. Serious injury or death can occur in a matter of minutes, particularly if a person's movement or breathing is restricted or loss of consciousness has occurred. In accordance with your fall rescue plan and appropriate first aid procedures it is essential to remove the person from the suspended position as quickly as possible.

In accordance with AS/NZS 1891.4:2009 clause 9.5

EQUIPMENT WHICH HAS ARRESTED A FALL OR SHOWS A DEFECT

Any piece of equipment including both personal and permanently installed items, which has been used to arrest a fall or which shows any defect during operator or periodic inspection shall be withdrawn from service immediately and a replacement obtained if necessary. A label indicating the condition or defect should be attached to the equipment, and it should be examined by a competent height safety installer who will decide whether the equipment is to be destroyed or repaired if necessary and returned to service. In the latter case, details of any repair shall be documented, and a copy given to the operator.



SafetyLink Pty Ltd | ABN 83 081 777 371 | www.safetylink.com

DISTRIBUTOR:

Asia-Pacific/The Americas | +61 2 4964 1068 | info@safetylink.com
Europe/Africa/Middle East | europe.sales@safetylink.com
Northern Europe | uk.sales@safetylink.com