



- ▲ SurfaceLink Anchor suits a multitude of roof profiles.
- ▲ Surface mounted anchors must not be used for rope access (abseiling).
- ▲ Install using 10 Rivets (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip).
- ▲ The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.

STANDARDS

Complies with AS/NZS 1891.4.

WHAT AM I USED FOR?

An anchor point designed for use on metal roof sheet profiles where access to timber is difficult. Adjustable design to suit different roof profiles.



SCAN ME
safetylink.com



SCAN ME
Catalogue



SCAN ME
Safety Centre
Training

COMPLETE UNIT - PRODUCT CODE: HSURF001+RIVETS			Weight: 1.501kg
Product Parts	Description	Qty	Material
EYEBOLT-SURFACELINK	SurfaceLink Eyebolt	1	316 Stainless Steel
NUT LOCKING HEX	Locking Hex Nut	1	316 Stainless Steel
ADV-PLATE-SS-305-H	SurfaceLink Plate: 305mm	1	316 Stainless Steel
WASHER 70OD-SS	Washer: 70 OD	1	316 Stainless Steel
SPRING WASHER M16	Spring Washer: M16	1	316 Stainless Steel
NUT M16	Nut: M16	1	316 Stainless Steel
FOAM-TAPE 29 cm	Adhesive single sided tape	2	Foam
RIVETS_8mm(27)	Rivets: 8mm	10	Alum

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-51 Version: 17.2