



The FrogLine Concrete Mounted System is a horizontal lifeline installed into concrete construction. The system is equipped with SafetyLink's engineered energy absorbing intermediate and end anchors to minimise loads on both the user and structure in the event of a fall. The continuous connection via the FrogLine Shuttle System on the 8mm stainless steel cable provides protection for up to four (4) users per system, two (2) users per span.

STANDARDS: The FrogLine has been tested and manufactured in accordance with AS/NZS 1891.2, ANSI Z359.6-2009, EN 795:2012, CEN/TS 16415:2013 and OSHA 1926.502.



FrogLine DonutLink
Video



FrogLine In Use
Video







Installation
Handbook



Catalogue



Safety Centre
Training

PRODUCT COMPONENTS	DESCRIPTION	MATERIAL	QTY	ANCHOR
END ANCHOR – PRODUCT CODE: STAT. FROGCAR002				
FROGLINE END	FrogLine Base End	316SS	1	
NUT M16	Nut: 16mm	316SS	1	
WASHER M16_SPRING	Spring Washer: M16	316SS	1	
WASHER M16_DONUT	Washer: DonutLink M16	316SS	1	
ROD M16x130mm	Anchor Rod M16x130mm (45 degree cut)	316SS	1	
INTERMEDIATE ANCHOR – PRODUCT CODE: STAT. FROGCAR001				
FROGLINE INT	FrogLine Base Intermediate	316SS	1	
NUT M16	Nut: 16mm	316SS	1	
WASHER M16_SPRING	Spring Washer: M16	316SS	1	
WASHER M16_DONUT	Washer: DonutLink M16	316SS	1	
ROD M16x130mm	Anchor Rod M16x130mm (45 degree cut)	316SS	1	
INTERMEDIATE EXT ANCHOR – PRODUCT CODE: STAT. FROGCAR008				
FROGLINE INT_EXT	FrogLine Base Intermediate Extended	316SS	1	
NUT M16	Nut: 16mm	316SS	1	
WASHER M16_SPRING	Spring Washer: M16	316SS	1	
WASHER M16_DONUT	Washer: DonutLink M16	316SS	1	
ROD M16x130mm	Anchor Rod M16x130mm (45 degree cut)	316SS	1	
CORNER ANCHOR – PRODUCT CODE: STAT. FROGCAR003				
FROGLINE CNR	FrogLine Base Corner	316SS	1	
NUT M16	Nut: 16mm	316SS	1	
WASHER M16_SPRING	Spring Washer: M16	316SS	1	
WASHER M16_DONUT	Washer: DonutLink M16	316SS	1	
ROD M16x130mm	Anchor Rod M16x130mm (45 degree cut)	316SS	1	

Rated 15kN one person anchor

- To comply with Australian/European Standards each unit must be tested after installation.
- Test consists of ultimate pull out force proof loading to 50% (7.5kN) of design purpose (15kN) of anchorage.
- Allow sufficient time for curing before testing, see instructions on fastener container.
- Recommended chemical anchor: Fischer FIS-V as per Fischer Product Supplement Data sheets.

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-527 Version: 9.0