

## **Aero-Bloc** Self Retracting Lifeline

## LIGHTWEIGHT COMPACT UNIT

Ergonomically designed to be used as a single person fall protection device. The Aero-Bloc's lightweight compact design fits comfortably to the users harness keeping the Aero-Bloc out of the workers way.

- ▲ Lightweight compact unit.
- ▲ Safety*Link*'s Aero-Bloc has a clear durable housing for ease of unit inspection.
- Letternal shock pack with durable cover.
- ▲ 140kg user rating when connecting to anchorages up to 600mm below the harness attachment location.
- Aluminium connectors with 16kN gate strength.
- Available in both Snap hook and Rebar hooks.
- ▲ Innovative quick connector available on the twin lifelines, allowing the users ease on connection.

Safety*Link* supply all height safety equipment to all industries buildings, commercial and industrial sites. From a series of anchor points to a complete network of systems for maintenance, cleaning access and inspections, Safety*Link* has you covered.

All Safety*Link* products undergo extensive testing in a multitude of scenarios by accredited testing facilities and comply to Australian and New Zealand standards.

Safety*Link's* experienced technical team is complemented with comprehensive installation manuals and testing certificates. We have national qualified installers keeping your assets safe.

## SafetyLink Pty Ltd 1300 789 545

+61 2 4964 1068 info@safetylink.com





## SafetyLink Aero-Bloc Collections

With Snap Hook	AEROBLOC2M-SH-KB	With Rebar Hook	AEROBLOC2M-RH-KB
	<ul> <li>Lightweight compact unit.</li> <li>SafetyLink's Aero- Bloc has a clear durable housing for ease of unit inspection.</li> <li>External shock pack with durable cover.</li> <li>140kg user rating.</li> <li>Aluminium connectors with 16kN gate strength.</li> <li>Snap hook.</li> </ul>		<ul> <li>Lightweight compact unit.</li> <li>SafetyLink's Aero- Bloc has a clear durable housing for ease of unit inspection.</li> <li>External shock pack with durable cover.</li> <li>140kg user rating.</li> <li>Aluminium connector with 16kN transverse rated gate.</li> <li>Rebar hook.</li> </ul>
Twin with Snap Hook	AEROBLOC2M-SH-X2	Twin with Rebar Hook	AEROBLOC2M-RH-X2
	<ul> <li>Lightweight compact unit.</li> <li>SafetyLink's Aero- Bloc has a clear durable housing for ease of unit inspection.</li> <li>External shock pack with durable cover.</li> <li>140kg user rating.</li> <li>Aluminium connectors with 16kN gate strength.</li> </ul>		<ul> <li>Lightweight compact unit.</li> <li>SafetyLink's Aero- Bloc has a clear durable housing for ease of unit inspection.</li> <li>External shock pack with durable cover.</li> <li>140kg user rating.</li> <li>Aluminium connector with 16kN transverse rated gate.</li> <li>Dual System with Rebar hooks.</li> </ul>
		<ul> <li>SafetyLink will provide you with the following:</li> <li>All products tested and manufactured to Australian and New Zealand Standards.</li> <li>All distributors and installers are trained to use SafetyLink products.</li> <li>Supply installation guides, testing results and product sheets.</li> <li>Layout Design Service providing compliant roof safety systems.</li> </ul>	

- ▲ Supply a large range of roof anchors that protect you from the ground up, allowing complete access to your roof.
- ▲ Installers are qualified to do yearly inspections on your anchors as per Australian and New Zealand Standards.



SafetyLink Pty Ltd **1300 789 545** +61 2 4964 1068 info@safetylink.com

bsi Guity Management Systems CERTIFIED