

TUFF-POST -600MM Concrete Mounted

TUFF-POST is a sealed unit made entirely from stainless steel. Designed to be submerged into garden beds, water and other mediums. **TUFF-POST** is used in conjunction with a Safety*Link* lifeline or energy absorbing eyebolt system.

- **TLFF-POST 600** is designed to raise the height of a height safety system 600mm off the ground.
- Designed to be anchored into concrete (steel bolted version available).
- Three sizes to choose from either 150mm, 300mm or 600mm TLIFF-POST.
- Suits positions like garden beds on roof tops.
- Must be chemically fastened.

Benefits of choosing Safety Link:

The **TUFF-POST** when installed with a lifeline is used with Safety*Link's* energy absorbing Frog*Line* Lifeline. The Frog*Line* Lifeline has advanced shock absorbing serpentines designed into each anchor with innovative built-in fall indicators. Therefore reducing the load off the structure and the person in the event of a fall.

The **TUFF-POST** can be used in conjunction with a horizontal lifeline or individual roof anchor.

When installing the **TUFF-POST** as an individual anchor Safety*Link's* Retro*Link* is installed onto the **TUFF-POST** creating a fall arrest / rope access anchor.

Load Testing of FrogLine with TUFF-POST



Safety*Link* will provide you with the following:

- All products tested and manufactured to Australian and New Zealand Standards.
- All distributors and installers are trained to use Safety *Link* products.
- Supply installation guides, testing results and product sheets.
- Layout Design Service providing compliant roof safety systems.
- Supply a large range of roof anchors that protect you from the ground up, allowing complete access to your roof.
- Installers are qualified to do yearly inspections on your anchors as per Australian and New Zealand Standards.



Safety Link Pty Ltd 1300 789 545

+61 2 4964 1068 info@safetylink.com



For further information and to order our products visit our website.

www.safetylink.com