



TUFF-BRACKET FrogLine Concrete Wall Mounted Tuff Bracket

- TUFF-BRACKET minimises potential water proofing issues by anchoring to a wall instead of garden bed floor.
- TUFF-BRACKET is designed to be submerged in garden beds, water and other medium walls.
- ▲ Must install with chemical adhesive.

PRODUCT COMPONENTS

WASHER M16_SPRING_316

FROGLINE END

NUT M16 316

TUFF-BRKT01

CON-M16x160

FROGLINE INT

NUT M16 316

TUFF-BRKT01

CON-M16x160

FROGLINE INT_EXT

WASHER M16_316

NUT M16_316

CON-M16x160

FROGLINE CNR

NUT M16 316

TUFF-BRKT01

CON-M16x160

TUFF-BRKT01

BOLT-M16x50mm-SS

WASHER M16_DONUT

BOLT-M16x50mm-SS

WASHER M16 DONUT

WASHER M16_SPRING_316

WASHER M16 316

WASHER M16_SPRING_316

BOLT-M16x50mm-SS

WASHER M16_DONUT

BOLT-M16x50mm-SS

WASHER M16 DONUT

WASHER M16_SPRING_316

WASHER M16_316

WASHER M16 316

The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent height safety installer that the structure is adequate. Refer to system information for site specific use.

FrogLine Base End

Spring Washer: M16

TUFF POST INTERMEDIATE ANCHOR - PRODUCT CODE: STAT.FROGTUFF001C-BRKT

Spring Washer: M16

Washer: DonutLink M16

TUFF POST INTERMEDIATE EXT ANCHOR - PRODUCT CODE: STAT.FROGTUFF008C-BRKT

Bolt: M16x50mm Set Screw

Washer: M16

Nut: M16

Tuff Bracket

Washer: M16

Nut: M16

Tuff Bracket

TUFF POST CORNER ANCHOR – PRODUCT CODE: STAT.FROGTUFF003C-BRKT

Washer: M16

Nut: M16

Tuff Bracket

Spring Washer: M16

Washer: DonutLink M16

FrogLine Base Corner

Spring Washer: M16

Washer: DonutLink M16

Bolt: M16x50mm Set Screw

Washer: DonutLink M16

FrogLine Base Intermediate

Bolt: M16x50mm Set Screw

Washer: M16

Nut: M16

Tuff Bracket

Bolt: M16x50mm Set Screw

TUFF POST END ANCHOR - PRODUCT CODE: STAT.FROGTUFF002C-BRKT

DESCRIPTION

Anchor Rod M16x160, Spring Washer & Nut

Anchor Rod M16x160, Spring Washer & Nut

Anchor Rod M16x160, Spring Washer & Nut

FrogLine Base Intermediate Extended



QTY

1

1

1

1

1

1

2

2

1

1

1

1

1

1

2

2

1

1

1

1

1

1

2

2

1

1

1

1

1

1

2

2

ANCHOR

MATERIAL

316SS

31655

316SS

316SS

316SS

316SS

316SS

316SS

316SS

316SS

31655

316SS

316SS

316SS

316SS

316SS

DATA SHEET



safetylink.com



FrogLine In Use Video

SCAN ME

Catalogue



Installation Handbook



Chemical Adhesive Data Sheet



Safety Centre

Training

Rated 15kN one person anchor

1. To comply with Australian/European Standards each TUFF-POST unit must be tested after installation.

Anchor Rod M16x160, Spring Washer & Nut

- 2. Test consists of ultimate pull out force proof loading to 50% (7.5kN) of design purpose (15kN) of anchorage.
- 3. Allow sufficient time for curing before testing, see instructions on fastener container.
- 4. Recommended chemical anchor: Fischer FIS-V as per Fischer Product Supplement Data sheets.

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.





© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on <u>ip@safetylink.com</u> and quote the product code.

Doc ID: MKT-946 Version: 4.0

Asia-Pacific/The Americas info@safetylink.com Europe/Africa/Middle East europe.sales@safetylink.com Northern Europe uk.sales@safetylink.com