



- ▲ Top Platform must be level with top of ladder rung (within 3 degrees).
- ▲ Step down to roof/ground must not exceed 300mm.
- ▲ Adjustable.
- ▲ Suitable for roof pitches 0 to 15 degrees only.
- ▲ FastFit ladder system is designed for single person use and rated for maximum 150kg.
- ▲ FastFit ladders are manufactured to AS 1657:2018 Standards.

COMPLETE UNIT - PRODUCT CODE: LADER002.PLT.TOP

Weight: 12kg

Product Code	Description	Material	Qty
LADER02.PLT.TOP.01	Top Platform Kit	Aluminium	1
SCREW 12-14x20mm	Screw: 12-14x20mm Self Tapping	Galvanised	12
BOLT-M8X60mm Cup HD	Bolt: M8x60mm Cup Head	316SS	2
NUT M8 Flanged_316	Flanged Nut: M8	316SS	2
RIVET_5x22mm	Rivet: 5 x 22mm	Aluminium	3
FOAM-TAPE-SQUARE	Foam Tape: 40x40x1.6mm	EPDM	3



Safety Centre
Training

Ladder Examples



LADERK002.012



LADERK002.012+BASE

A FALL RESCUE PLAN SHOULD BE DEVELOPED PRIOR TO USING SAFETYLINK EQUIPMENT

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-902 Version: 6.0