



Example; Ladder attached to parapet



- ▲ Ladder Stiffeners should be used on your installation if a building has very large eaves or a facade has a large overhang that brings the ladder out away from any structure to fix to. For example, hatch ladders with no fixing brackets.
- ▲ Heavy gauge aluminium for superior strength.
- ▲ FastFit ladder system is designed for single person use and rated for maximum 150kg.
- ▲ FastFit ladders are manufactured to AS 1657:2018 Standards.

| COMPLETE UNIT - PRODUCT CODE: LADER002.STF.1200 | | Weight: 4.5kg | |
|---|---|---------------|-----|
| Components | Description | Material | Qty |
| LADER002.STF.1200.01 | Ladder Stile Strengthening Bars: 1200mm | Aluminium | 2 |
| BOLT-M8x60mm Cup HD | Bolt: M8x60mm Cup HD 316SS | 316SS | 14 |
| NUT M8 Flanged_316 | Nut: M8 Flanged 316SS | 316SS | 14 |

| COMPLETE UNIT - PRODUCT CODE: LADER002.STF.1800 | | Weight: 6.4kg | |
|---|---|---------------|-----|
| Components | Description | Material | Qty |
| LADER002.STF.1800.01 | Ladder Stile Strengthening Bars: 1800mm | Aluminium | 2 |
| BOLT-M8x60mm Cup HD | Bolt: M8x60mm Cup HD 316SS | 316SS | 18 |
| NUT M8 Flanged_316 | Nut: M8 Flanged 316SS | 316SS | 18 |

| COMPLETE UNIT - PRODUCT CODE: LADER002.STF.2400 | | Weight: 7.6kg | |
|---|---|---------------|-----|
| Components | Description | Material | Qty |
| LADER002.STF.2400.01 | Ladder Stile Strengthening Bars: 2400mm | Aluminium | 2 |
| BOLT-M8x60mm Cup HD | Bolt: M8x60mm Cup HD 316SS | 316SS | 18 |
| NUT M8 Flanged_316 | Nut: M8 Flanged 316SS | 316SS | 18 |

A FALL RESCUE PLAN SHOULD BE DEVELOPED PRIOR TO USING SAFETYLINK EQUIPMENT

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-1077 Version: 3.0