



CLASSIC TUFF-POST FrogLine 300mm (Square) Concrete Mounted



- ▲ TUFF-POST is designed to raise the height of a Frogline Lifeline system 300mm.
- ▲ TUFF-POST is made entirely from 316 stainless steel.
- ▲ Designed to be submerged into garden beds, water and other mediums.
- ▲ Designed to be **anchored into concrete** (steel bolted version available).

The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent height safety installer that the structure is adequate. Refer to system information for site specific use.



SCAN ME

safetylink.com



SCAN ME

FrogLine In Use
Video



SCAN ME

Catalogue



SCAN ME

Installation
Handbook



SCAN ME

Chemical Adhesive
Data Sheet



SCAN ME

Safety Centre
Training

PRODUCT COMPONENTS		DESCRIPTION	MATERIAL	QTY	ANCHOR
TUFF POST END ANCHOR – PRODUCT CODE: STAT.FROGTUFF002C-300					
FROGLINE END	FrogLine Base End		316SS	1	
BOLT-M16x50mm-SS	Bolt: M16x50mm Set Screw		316SS	1	
WASHER M16_SPRING	Spring Washer: M16		316SS	1	
WASHER M16_DONUT	Washer: DonutLink M16		316SS	1	
TUFF-POST300	TUFF-POST 300mm (Square)		316SS	1	
CON-M12x160	Anchor Rod M12X160, Nut, Spring Washer, Washer		316SS	4	
TUFF POST INTERMEDIATE ANCHOR – PRODUCT CODE: STAT.FROGTUFF001C-300					
FROGLINE INT	FrogLine Base Intermediate		316SS	1	
BOLT-M16x50mm-SS	Bolt: M16x50mm Set Screw		316SS	1	
WASHER M16_SPRING	Spring Washer: M16		316SS	1	
WASHER M16_DONUT	Washer: DonutLink M16		316SS	1	
TUFF-POST300	TUFF-POST 300mm (Square)		316SS	1	
CON-M12x160	Anchor Rod M12X160, Nut, Spring Washer, Washer		316SS	4	
TUFF POST INTERMEDIATE EXT ANCHOR – PRODUCT CODE: STAT.FROGTUFF008C-300					
FROGLINE INT_EXT	FrogLine Base Intermediate Extended		316SS	1	
BOLT-M16x50mm-SS	Bolt: M16x50mm Set Screw		316SS	1	
WASHER M16_SPRING	Spring Washer: M16		316SS	1	
WASHER M16_DONUT	Washer: DonutLink M16		316SS	1	
TUFF-POST300	TUFF-POST 300mm (Square)		316SS	1	
CON-M12x160	Anchor Rod M12X160, Nut, Spring Washer, Washer		316SS	4	
TUFF POST CORNER ANCHOR – PRODUCT CODE: STAT.FROGTUFF003C-300					
FROGLINE CNR	FrogLine Base Corner		316SS	1	
BOLT-M16x50mm-SS	Bolt: M16x50mm Set Screw		316SS	1	
WASHER M16_SPRING	Spring Washer: M16		316SS	1	
WASHER M16_DONUT	Washer: DonutLink M16		316SS	1	
TUFF-POST300	TUFF-POST 300mm (Square)		316SS	1	
CON-M12x160	Anchor Rod M12X160, Nut, Spring Washer, Washer		316SS	4	

Rated 15kN one person anchor

1. To comply with Australian/European Standards each TUFF-POST unit must be tested after installation.
2. Test consists of ultimate pull out force proof loading to 50% (7.5kN) of design purpose (15kN) of anchorage.
3. Allow sufficient time for curing before testing, see instructions on fastener container.
4. Recommended chemical anchor: Fischer FIS-V as per Fischer Product Supplement Data sheets.

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-596 Version: 6.0