












Ergonomically designed to be used as a single person fall protection device. The Aero-Bloc's lightweight compact design fits comfortably to the users harness keeping the Aero-Bloc out of the workers way.

- ▲ SafetyLink's Aero-Bloc has a clear durable housing for ease of unit inspection.
- ▲ External shock pack with durable cover.
- ▲ 140kg user rating when connecting to anchorages up to 600mm below the harness attachment location.
- ▲ Aluminium connectors with 16kN gate strength.
- ▲ Available in both Snap hook and Rebar hooks.
- ▲ Innovative quick connector available on the dual system, allowing the users ease on connection.
- ▲ Certified to EN360:2002.

Figure 1

	ANCHORAGE CONNECTOR	HARNES CONNECTOR	SINGLE/TWIN	WEIGHT (kg)
PRODUCT CODE				
	4	N/A	S	1.0
	5	N/A	S	1.3
	4	3	S	1.3
	5	3	S	1.6
	4	6	S	1.3
	5	6	S	1.6
	4	6	T	2.3
	5	6	T	2.9

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-601 Version: 11.0



SCAN ME
safetylink.com



SCAN ME
Catalogue



SCAN ME
Safety Centre
Training