

- ▲ Ladder cages are highly recommended for ladders over 3.5 metres.
- ▲ Cage must start between 2000 to 2200mm above base of ladder.
- ▲ At the top of ladder, the cage shall extend not less than 1 metre above platform or to the top of the guard railing if installed.
- ▲ Ladder cage bars can be cut to achieve required length of the cage.
- ▲ Additional holes are present to allow adjustment in 150mm increments.
- ▲ Heavy gauge aluminium for superior strength.
- ▲ Install with supplied M8 Bolts, Nuts and Washers.
- ▲ FastFit ladder system is designed for single person use and rated for maximum 150kg.
- ▲ FastFit ladders are manufactured to AS 1657:2018 Standards.



SCAN ME
Manual



SCAN ME
Website



SCAN ME
Catalogue



SCAN ME
Safety Centre
Training

Product Code	Description	Length
LADER002.CAGE.2	Ladder Cage (0 to 2.0 Metres)	2 metres
LADER002.CAGE.3	Ladder Cage (2.01 to 3.0 Metres)	3 metres
LADER002.CAGE.4	Ladder Cage (3.01 to 4.0 Metres)	4 metres
LADER002.CAGE.5	Ladder Cage (4.01 to 5.0 Metres)	5 metres


Ladder examples below



LADERK002.042



LADERK002.042+BASE



LADERK002.052



LADERK002.052+BASE

A FALL RESCUE PLAN SHOULD BE DEVELOPED PRIOR TO USING SAFETYLINK EQUIPMENT

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-890 Version: 8.0