



TAKE YOUR NEXT STEP WITH CONFIDENCE

YOUR EVERYDAY SOLUTION FOR COMFORT AND SAFETY AT HEIGHTS

Easy to use



Quick connect buckles for easy usage on the harness.

Safety



All harnesses are certified to Australian and New Zealand standards

Comfort



Breathable comfort shoulder padding and waist belt with thermocompressed backing for extra support.

HARNESSES



WAU HAR32M S/M/L XL/XXL



Two (2) fall arrest anchorage points (back/front). Five (5) adjustment locations, including three (3) quick connect buckles and two (2) torso adjusters. Breathable comfort shoulder padding. Visual fall indicator for easy inspection. Two (2) locations for parking unused lanyard legs. Certified to AS/NZS1891.1:2020.



WAU HAR35M S/M/L XL/XXL



Two (2) fall arrest attachment points (back/front). Six (6) adjustment locations, including four (4) quick connect buckles and 2 torso adjusters. Comfort waist belt with thermocompressed backing for extra support. Work positioning side waist attachment points (pole strap use). One (1) total restraint attachment point (rear waist). Breathable comfort shoulder padding. Visual fall indicator for easy inspection. Two (2) locations for parking unused lanyard legs. Certified to AS/NZS1891.1:2020.



WAU HAR12 S/M/L XL/XXL



Two (2) fall arrest anchorage points (back/front). Two (2) adjustment locations, including two (2) pass thru buckles. Visual fall indicator for easy inspection. Four (4) locations for parking unused lanyard legs. Ideal for construction and maintenance. Certified to AS/NZS1891.1:2020.



WAU HAR14 S/M/L XL/XXL



Two (2) fall arrest anchorage points (back/front). Three (3) adjustment locations, including three (3) pass thru buckles. Comfort waist belt with work positioning side waist attachment points (pole strap use). Visual fall indicator for easy inspection. Four (4) locations for parking unused lanyard legs. Ideal for construction and maintenance.

LANYARDS



WAUAN203200NN

Single Lanyard with Energy Absorber

The harness connector is a karabiner, and the anchor connector is also a karabiner, both connected by orange webbing. Connectors have 16kN gate strength



WAUAN235200JJ

Single Lanyard (Elastic Webbing) with Energy Absorber with attachment rebar bar. The harness connector is snap hook, and the anchor connector is also a snap hook, both connected by elasticised black webbing with orange fleck. Connectors have 16kN gate strength



WAUAN235200NN

Single Lanyard (Elastic Webbing) with Energy Absorber

The harness connector is a karabiner, and the anchor connector is also a karabiner, both connected by elasticised black webbing with orange fleck. Connectors have 16kN gate strength



WAUAN235200JW

Single Lanyard with Tear Web Energy Absorbing and Elasticised Leg

The harness connector is snap hook, and the anchor connector is a rebar hook, both connected by elasticised black webbing with orange fleck. Connectors have 16kN gate strength



WAUAN245200JWW

Twin Lanyard (Elastic Webbing) with Energy Absorber

The harness connector is snap hook, and the twin anchor connectors are rebar hooks, both connected by elasticised black webbing with orange fleck. Connectors have 16kN gate strength

