




- ▲ Essential entry point system to stabilise your ladder.
- ▲ Quick and easy installation.
- ▲ To extend beyond box gutters and larger areas.
- ▲ 980mm gutter to end, overall length 1115mm.
- ▲ LadderLinks have a protective membrane in the form of a powdercoat finish, this ensures your LadderLink is ready for use and ready for any additional colour matching you apply.
- ▲ LadderLinks are rated to 150kg and must only be installed to structures and fixings capable of supporting 150kg.

WHAT AM I USED FOR?

Essential entry point system to any height safety system. Made from marine grade aluminium the LadderLink is designed to support a ladder, stopping sideways movement and therefore holding the ladder in place safely.



SCAN ME

www.safetylink.com



SCAN ME

Catalogue



SCAN ME

Safety Centre
Training

COMPLETE UNIT - PRODUCT CODE: LADFX002

Product Parts	Description	Qty	Weight (kg)	Material
LADFX002	Ladderink: Extended	1	6.6	Marine Grade Aluminium

- ⚠ Adjusting the pitch of the LadderLink is to be done by a sheet metal fabricators' bending machine. LadderLink is made from high tensile aluminium therefore ensure the bender is set on a high radius to prevent cracking.
- ⚠ Protective coating must not be removed.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-86 Version: 14.0