




- ⚠ Essential entry point system to stabilise your ladder stopping sideways movement and therefore holding the ladder in place safely.
- ⚠ Quick and easy installation, in addition the LadderLink bracket has two tie off points to aid in securing the ladder in position.
- ⚠ LadderLinks have a protective membrane in the form of a powdercoat finish, this ensures your LadderLink is ready for use and ready for any additional colour matching you apply.
- ⚠ LadderLinks are rated to 150kg and must only be installed to structures and fixings capable of supporting 150kg.

WHAT AM I USED FOR?

Essential entry point system to any height safety system. Made from marine grade aluminium the LadderLink is designed to support a ladder, stopping sideways movement and therefore holding the ladder in place safely.




www.safetylink.com



Catalogue



Safety Centre
Training



COMPLETE UNIT - PRODUCT CODE: LADFX001

Product Parts	Description	Qty	Weight (kg)	Material
LADFX001	Ladderlink: Standard	1	2.290	Marine Grade Aluminium

- ⚠ Adjusting the pitch of the LadderLink is to be done by a sheet metal fabricators' bending machine. LadderLink is made from high tensile aluminium therefore ensure the bender is set on a high radius to prevent cracking.
- ⚠ Protective coating must not be removed.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-90 Version: 16.0