



- ▲ Concretelink is a fall arrest and rope access anchor designed for use in concrete, where the eyebolt will remain exposed for attachment.
- ▲ Must be chemically fastened, recommended chemical is Fischer FIS-V.
- ▲ The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.
- ▲ Eyelet 35mm ID.

STANDARDS

Complies with AS/NZS 1891.4 and AS/NZS 5532-2013.

COMPLETE UNIT - PRODUCT CODE: CONCL002

Product Parts	Description	Qty	Material
CON-INSERT	Concrete Insert	1	316 Stainless Steel
EYEBOLT M16x26mm	Collared Eyebolt: M16x26mm	1	316 Stainless Steel

Standard Compliance

Manufacturing Standard

This concrete anchor is compliant with AS5532:2025 and can be loaded in the directions shown in the product instruction handbook, download copy at www.safetylink.com.

Selection, Use and Maintenance Standard

To be compliant with AS/NZS1891.4:2025, when fixed with Chemical or Friction fasteners into concrete, all single fix concrete anchor shall be proof tested annually to 50% of its design load. Records of this proof test shall be kept and made available for future inspections. For multi fix concrete anchor an exemption may apply from annual proof testing if the appropriate information and documentation have been recorded at the time of installation and is available for future inspections. See AS/NZS1891.2025 Section 8 for further details.

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-27 Version: 20.0

