

FROGLINK - Surface Mounted Anchor with First Man Up Strop



- Fast simple unit for installation, fall protection whilst working at heights.
- Low profile reflective design is a plus for any commercial or residential enterprise wanting to maintain an aesthetically pleasing façade.
- Can be fixed to a corrugated sheet metal, trimdek, kliplok and a multitude of other metal roof sheeting materials, can be used for domestic or commercial use.
- Dynamic design reduces the load back onto the structure and person attached to the anchor.
- Designed to suit all roof profiles with a single row of attachment holes for the rivets.
- Install using 7 x Tri-fold Rivets, RV6605-9-6W (Drill Size 7.8-8.2mm, 27.7mm length, 1.0-9.5mm grip range, Aluminium).
- One person anchor rated to 15kN.
- The first man up Strop is used as a first man up system; reduces the amount of entry access anchors required. The Quicklink must be attached to a load rating anchor.
- Attachment end should be secured with a strop hook when not in use to ensure it can be accessed from a safe area for next use.
- UV plastic coated to prevent wear on roof sheeting.

WHAT AM I USED FOR?

A surface mounted height safety anchor point for use on metal roof profiles where access to timber is difficult will arrest from any direction.



STANDARDS

Complies with AS/NZS 1891.4, AS/NZS 5532-2013, EN 795:2012 and OSHA 1926.502.

PRODUCT CODE	DESCRIPTION	Weight (kg)
FROGL001+STROP_swaged	FROGL001+STROP (swaged): 1 x FrogLink 1 x 1.2m strop swaged to FrogLink 1 x Strophook with warning tag	0.339
FROGLINK+STROP+RIVETS_swaged	FROGL001+STROP (swaged) with 7 Aluminium Rivets	0.388

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-192 Version: 16.0

