

SafetyLink's PigLink is a Lateral Restraint for guiding ropes on a long descent.

PigLink's should be installed at intervals of between 20m and 30m to restrain an abseiler's lateral movement. Depending on the application, smaller intervals may be required.

⚠ The PigLink is not a single point anchor.

All safety procedures must comply in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety system.

PigLink Rope Guide M12x120mm (Concrete Mounted):



PRODUCT CODE: PIGLK001

Product Parts	Description	Qty	Material
PIGLK001	PigLink Rope Guide - M12x120mm	1	316 Stainless Steel

PigLink Rope Guide M12x120mm (Steel Mounted):



PRODUCT CODE: PIGLK002

Product Parts	Description	Qty	Material
PIGLK001	PigLink Rope Guide - M12x120mm	1	316 Stainless Steel
NUT M12 Flanged_316	Nut: M12 Flanged	2	316 Stainless Steel

PigLink Rope Guide M12x120mm (Conceal Mounted):



PRODUCT CODE: PIGLK003

Product Parts	Description	Qty	Material
PIGLK001	PigLink Rope Guide - M12x120mm	1	316 Stainless Steel
STEELINK-M12.02	Base Cap, M12, SteelLink	1	316 Stainless Steel
STEELINK-M12.01	End Cap, M12x1.75 SteelLink	1	316 Stainless Steel
NUT M16_316	Nut: M16	1	316 Stainless Steel
WASHER M12_Spring_316	Washer: M12 Spring	1	316 Stainless Steel
WASHER M12_316	Washer: M12	1	316 Stainless Steel
NUT M12_316	Nut: M12	1	316 Stainless Steel



SCAN ME

www.safetylink.com



SCAN ME

Catalogue



SCAN ME

Safety Centre
Training

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-1265 Version: 3.0