



- ▲ SafetyLink's patented WindowLink is an anchor point designed for use in concrete structures where the eyebolt will remain concealed until needed for use.
- ▲ The WindowLink can be placed outside or within the building, creating easy access for window maintenance.
- ▲ Non obtrusive concrete anchor designed to swivel 360 degrees.
- ▲ Discreet stainless steel cover.
- ▲ Must be chemically fastened, recommended chemical is Fischer FIS-V.

STANDARDS

Complies with AS/NZS 1891.4 and EN 795:2012.

COMPLETE UNIT - PRODUCT CODE: WINDW001

Product Parts	Description	Qty	Weight (kg)	Material
WINDW001	WindowLink Complete Unit/Floor-Wall Link	1	0.474	316 SS

Standard Compliance

Manufacturing Standard

This concrete anchor is compliant with AS5532:2025 and can be loaded in the directions shown in the product instruction handbook, download copy at www.safetylink.com.

Selection, Use and Maintenance Standard

To be compliant with AS/NZS1891.4:2025, when fixed with Chemical or Friction fasteners into concrete, all single fix concrete anchor shall be proof tested annually to 50% of its design load. Records of this proof test shall be kept and made available for future inspections. For multi fix concrete anchor an exemption may apply from annual proof testing if the appropriate information and documentation have been recorded at the time of installation and is available for future inspections. See AS/NZS1891.2025 Section 8 for further details.

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



SCAN ME

safetylink.com



SCAN ME

Catalogue



SCAN ME

Safety Centre
Training

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-94 Version: 18.0