



- ▲ Purlin anchor is used for overhead application.
- ▲ 360° Multi-directional.
- ▲ Single person anchor, rated at 15kN.

STANDARDS

Complies with AS/NZS 1891.4.



All safety procedures must comply in accordance with the current safety code(s) of practice(s) for working at heights. Ensure safety at all times during and after installation by using an appropriate height safety system.



SCAN ME

safetylink.com



SCAN ME

Catalogue



SCAN ME

Safety Centre
Training

COMPLETE UNIT - PRODUCT CODE: PURLINAB_RL

Product Parts	Description	Qty	Material
EYEBOLT M16x26mm	Eyebolt: M16x26mm	1	316 Stainless Steel
WASHER 70od_SS	Washer: 70OD	1	316 Stainless Steel
WASHER M16_316	Washer: M16	1	316 Stainless Steel
WASHER M16_Spring_316	Spring Washer: M16	1	316 Stainless Steel
NUT M16_316	Nut: M16	1	316 Stainless Steel
RAFTER-BASE	RafterLink Base Plate (0 Degree Pitch)	1	316 Stainless Steel
Rivet_8mm(27.7)	Rivets: 8mm	8	Aluminium

All products must be installed in accordance with SafetyLink's installation handbook, using only products supplied by SafetyLink Pty Ltd.



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-1127 Version: 4.0