



Terms and Conditions



Website

DATA SHEET

CONCRETELINK

One Piece Concrete Mounted Anchor



- ConcreteLink anchor with low profile eyebolt.
- Must be chemically fastened.

STANDARDS

Complies with AS/NZS 1891.4 and AS/NZS 5532-2013.

WHAT AM I USED FOR?

An anchor point designed for use in concrete, where the eyebolt will remain exposed for attachment.

The building or structure for the anchorages must be assessed by an engineer, unless it is clear to a competent person that the structure is adequate.

Testing for Free fall-arrest for one person. 15 kN ultimate strength

1. To comply with Australian Standards each ConcreteLink unit must be tested after installation.
2. Allow sufficient time for curing before testing, see instructions on fastener container.
3. Test consists of ultimate pull out force proof loading to 50% of design purpose of anchorage.
4. Recommended chemical anchor: Hilti RE500 or Hilti HY200 as per Hilti Product Supplement Data Sheets. Read instructions on product carefully. The entire surface of the ConcreteLink unit that is in contact with the concrete must have sufficient adhesive gel, as specified on the product.

COMPLETE UNIT - PRODUCT CODE: CONCL005

Product Parts	Description	Qty	Weight	Material
CONCL005	ConcreteLink One Piece Unit: 100mm, M16	1	.332g	316 Stainless Steel



© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Version 05.18